

Z EAST - [Untitled1:1]

File View Edit Tools Window Help

Drafts Pending Active

- L3: (5809) 725/\$.ccls.
- L4: (32) 3 and (DMA and PCI)
- L5: (0) 4 and (valid near5 video near5 data)
- L6: (17) (valid near5 video near5 data) and (DMA and PCI)
- L7: (13) 6 and (memory near5 address)
- L8: (0) 7 and (valid near5 command)
- L9: (6) 7 and (command near3 signal)
- L10: (0) 9 and (address adj queue)
- L11: (6) 9 and valid
- L12: (6) 11 and ((control\$4 or command) adj signal)
- L13: (37871) video near3 process\$3

Failed Saved Favorites Tagged (4) UDC Queue Trash

Search List Browse Queue Clear DBs USPAT; US-PGPUB; EPO Default operator: OR Duals Highlight all hit terms initially

11 and ((control\$4 or command) adj signal)

BRS form IS&R form Image Text HTML


| | U | I | Document ID | Issue Date | Pages | Title | Current OR | Current XRef | Retrieval Classif |
|---|--------------------------|-------------------------------------|---------------|------------|-------|---|------------|------------------------|-------------------|
| 1 | <input type="checkbox"/> | <input type="checkbox"/> | US 6188381 B1 | 20010213 | 26 | Modular parallel-pipelined vision system for real-time video processing | 345/581 | 345/554; 345/633; | V |
| 2 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5854640 A | 19981229 | 32 | Method and apparatus for byte alignment of video data in a memory of a host system | 345/547 | 345/566 | N |
| 3 | <input type="checkbox"/> | <input type="checkbox"/> | US 5777624 A | 19980707 | 32 | Method and apparatus for eliminating visual artifacts caused by diffusing errors in a decimal | 345/605 | | M |
| 4 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5760794 A | 19980602 | 34 | Method for storing video data in a plurality of video data buffers on a host | 345/522 | 345/565 | M |
| 5 | <input type="checkbox"/> | <input type="checkbox"/> | US 5699277 A | 19971216 | 33 | Method and apparatus for source clipping a video image in a video delivery system | 345/725 | 345/625; 348/14.07; | L |
| 6 | <input type="checkbox"/> | <input type="checkbox"/> | US 5426739 A | 19950620 | 38 | Local bus - I/O Bus Computer Architecture | 710/305 | | |

His Details HTML NUM

Ready

HEAST - [Untitled1:1]

File View Edit Tools Window Help



- Drafts
- Pending
- Active

- L3: (5809) 725/\$.ccls.
- L4: (32) 3 and (DMA and PCI)
- L5: (0) 4 and (valid near5 video near5 data)
- L6: (17) (valid near5 video near5 data) and (DMA and PCI)
- L7: (13) 6 and (memory near5 address)
- L8: (0) 7 and (valid near5 command)
- L9: (6) 7 and (command near3 signal)
- L10: (0) 9 and (address adj queue)
- L11: (6) 9 and valid
- L12: (6) 11 and ((control\$4 or command) adj signal)
- L13: (37871) video near3 process\$3
- L14: (6313) 13 and interconnect\$3
- L15: (344) 14 and (DMA and PCI)
- L16: (227) 15 and ((control\$4 or command) adj signal)
- L17: (8) 16 and (valid near5 video near5 (data or signal))
- L18: (7) 17 and (memory near5 address\$3)

- Failed
- Saved
- Favorites
- Tagged (5)

Search List Browse Queue Clear

DB: USPAT;US-PPGPUB;EPO Plurals Highlight all hit terms initially

Default operator: DR

17 and (memory near5 address\$3)

BRS form I56R form Image Text HTML

| | U | I | Document ID | Issue Date | Pages | Title | Current OR | Current XRef | Retrieval Classif |
|---|--------------------------|-------------------------------------|---------------|------------|-------|---|------------|------------------------|-------------------|
| 1 | <input type="checkbox"/> | <input type="checkbox"/> | US 6295546 B1 | 20010925 | 118 | Method and apparatus for eliminating the transpose buffer during a decomposed forward transform-based picture | 708/402 | 708/401 | A |
| 2 | <input type="checkbox"/> | <input type="checkbox"/> | US 6292589 B1 | 20010918 | 98 | Method for choosing rate control parameters in motion-compensated transform-based picture | 382/239 | 348/416.1; 382/238; | C |
| 3 | <input type="checkbox"/> | <input type="checkbox"/> | US 6101276 A | 20000808 | 97 | Method and apparatus for performing two pass quality video compression through pipeline | 382/236 | | A |
| 4 | <input type="checkbox"/> | <input type="checkbox"/> | US 6026217 A | 20000215 | 119 | Method and apparatus for eliminating the transpose buffer during a decomposed forward transform-based picture | 709/247 | 710/1; 710/29; | A |
| 5 | <input type="checkbox"/> | <input type="checkbox"/> | US 5995080 A | 19991130 | 120 | Method and apparatus for interleaving and de-interleaving YUV pixel data | 345/603 | 345/530; 345/555; | B |
| 6 | <input type="checkbox"/> | <input type="checkbox"/> | US 5968153 A | 19991019 | 20 | Mechanism for high bandwidth DMA transfers in a PCI environment | 710/110 | 710/113; 710/117; | V |
| 7 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5884050 A | 19990316 | 21 | Mechanism for high bandwidth DMA transfers in a PCI environment | 710/107 | 710/22; 710/52 | V |

Hits Details HTML

NUM

Ready

- L1: (3446) 725/\$.ccls.
- L2: (864) 1 and (video adj data)
- L3: (84) 2 and (command adj data)
- L4: (13) 3 and (memory adj address)
- L5: (11) 4 and (output and receiver)
- L6: (2) 5 and (request near5 signal)
- L7: (10) 4 and (output near3 interface)
- L8: (9) 7 and (transfer\$3 near3 data)
- L9: (5) 8 and (response near8 request)
- L10: (5) 9 and memory
- L11: (0) 10 and (queue near5 memory)
- L12: (0) 10 and (queue same memory)
- L13: (5) 10 and (input near5 interface)

Failed

 USPAT PluralsDefault operator: OR Highlight all hit terms initially

10 and (input near5 interface)

| | U | I | Document ID | Issue Date | Pages | Title | Curr |
|---|--------------------------|--------------------------|--------------|------------|-------|---|---------|
| 1 | <input type="checkbox"/> | <input type="checkbox"/> | US 6018765 A | 20000125 | 29 | Multi-channel multimedia data server | 709/217 |
| 2 | <input type="checkbox"/> | <input type="checkbox"/> | US 5761417 A | 19980602 | 36 | Video data streamer having scheduler for scheduling read request for individual data buff | 709/231 |
| 3 | <input type="checkbox"/> | <input type="checkbox"/> | US 5712976 A | 19980127 | 36 | Video data streamer for simultaneously conveying same one or different ones of data b | 725/115 |



- L5: (11) 4 and (output and receiver)
- L6: (2) 5 and (request near5 signal)
- L7: (10) 4 and (output near3 interface)
- L8: (9) 7 and (transfer\$3 near3 data)
- L9: (5) 8 and (response near8 request)
- L10: (5) 9 and memory
- L11: (0) 10 and (queue near5 memory)
- L12: (0) 10 and (queue same memory)
- L13: (5) 10 and (input near5 interface)

Failed

Default operator:

OR

Highlight all hit terms initially

10 and (input near5 interface)

| | U | I | Document ID | Issue Date | Pages | Title | Current |
|---|--------------------------|--------------------------|--------------|------------|-------|---|---------|
| 1 | <input type="checkbox"/> | <input type="checkbox"/> | US 6018765 A | 20000125 | 29 | Multi-channel multimedia data server | 709/217 |
| 2 | <input type="checkbox"/> | <input type="checkbox"/> | US 5761417 A | 19980602 | 36 | Video data streamer having scheduler for scheduling read request for individual data buff | 709/231 |
| 3 | <input type="checkbox"/> | <input type="checkbox"/> | US 5712976 A | 19980127 | 36 | Video data streamer for simultaneously conveying same one or different ones of data b | 725/115 |
| 4 | <input type="checkbox"/> | <input type="checkbox"/> | US 5586264 A | 19961217 | 36 | Video optimized media streamer with cache management | 725/115 |
| 5 | <input type="checkbox"/> | <input type="checkbox"/> | US 5321750 A | 19940614 | 84 | Restricted information distribution system apparatus and methods | 380/230 |

EAST - [kbc128.wsp:1]

File View Edit Tools Window Help

Drafts
BRS:
Pending
Active
L1: (3446) 725/\$.ccls.
L2: (864) 1 and (video adj data)
L3: (84) 2 and (command adj data)
L4: (13) 3 and (memory adj address)
L5: (11) 4 and (output and receiver)
L6: (2) 5 and (request near5 signal)
Failed
Saved

Search List Browse Queue Clear
DBs USPAT Plurals
Default operator: OR Highlight all hit terms initially

5 and (request near5 signal)

BRS form IS&R form Image Text HTML

| | U | I | Document ID | Issue Date | Pages | Title | Current |
|---|--------------------------|--------------------------|--------------|------------|-------|--|---------|
| 1 | <input type="checkbox"/> | <input type="checkbox"/> | US 5740028 A | 19980414 | 97 | Information input/output control device and method therefor | 725/149 |
| 2 | <input type="checkbox"/> | <input type="checkbox"/> | US 5321750 A | 19940614 | 84 | Restricted information distribution system apparatus and methods | 380/230 |

Hits Details HTML